THE PRINCIPLE

FISO's temperature probes for medical applications are based on white light absorption and transmission by a GaAs (gallium arsenide) semiconductor. The effects of the temperature variations on this semiconductor are well-known and predictable. As the temperature of the semiconductor increases, the transmission spectrum (i.e. the light that is not absorbed) is reduced by longer wavelengths (i.e. more longer wavelengths are absorbed). At any given temperature, transmission essentially jumps from 0% to 100% at a specific wavelength. This jump is called the absorption shift, and the relationship between a specific wavelength -where the absorption shift takes place- and the temperature is therefore predictable.

This shift occurs because of the variation into the semiconductor's energy band gap. This "gap" refers to the energy required to bump the electrons in the material into an excited state (as opposed to the relaxed, steady state). As more energy enters the semiconductor, in the form of heat as its temperature rises, the gap gets narrower –which means that less additional energy is required to excite an electron. The photons (particles of light) entering the semiconductor are what actually excite the electrons. If a photon is carrying enough energy to get an electron across the gap, it will be absorbed. If it does not carry enough energy, then it will be transmitted. The shorter a photon's wavelength is, the more energy it carries. Since the band gap narrows as the semiconductor's temperature increases, less energy will be required to jump across the gap, and photons with less and less energy (longer and longer wavelengths) will be absorbed "by the band", as they say. Consequently, measuring the position of the absorption shift gives a measure of the semiconductor's temperature. It is important to note that this technology is wavelength dependent instead of intensity dependent.

THE TEMPERATURE SENSOR

FISO's temperature probes are based on the direct contact. Traditional temperature sensors such as thermocouples and RTDs (resistance temperature devices) work on the same principle. In other words, the semiconducting material must be touching the object or be immersed in the liquid or gas to be measured in order to give a reading. The more intimate the contact and the smaller the thermal mass of the sensing tip are, the faster the semiconductor will respond to temperature changes.

Tiny GaAs semiconductor is bonded to one end of an optical fiber. On one side of this semiconductor, a reflective dielectric film (material that does not conduct electricity) is installed. All the materials share this property ("high dielectric strength"), which is one of the principal advantages over traditional temperature which use wire to convey an electrical signal. The length of the optical fiber is covered with a protective nylon, polyimide, PTFE or custom cable, making it resistant to handling.



The computation of the absorption shift does not depend on signal intensity for this particular technology, but only the wavelengths of the light are of interest. Thus, the various factors that contribute to the signal attenuation in the optical fiber (fiber length, number and quality of connections, fiber diameter and composition, bending) do not impose any serious constraints to the system. FISO's approach gives reliable, repeatable temperature measurements without the errors that may result from a loss of power in the connectors or a sharp bend in the optical fiber.



深 圳 市 新 世 联 科 技 有 限 公 司

地址：深圳市深南中路2066号华能大厦712室
电话：0755-83680810 83680820 83680830 83680860
网址：www.apollounion.com
邮编：518031
传真：0755-83680866
邮箱：sales@apollounion.com

Apollosense®

Single Point Temperature Sensors

MEDICAL

SPECIFICATIONS

Temperature range	10°C to 90°C *(range may be extended to –20 to 200 °C)* [1]
Resolution	0.1°C rms
System accuracy[2]	±0.5°C
Bending radius	10mm
Response time[3]	25msec / 100msec
Cable sheathing	Nylon Sheathing, OD: 0.9 mm; custom cable are possible
Tip termination	Bare / Sheathed with gel / Custom design possible
Standard sensor length	2 meters / Custom length possible
Connector	FC-APC with smart key communicating calibration data to the reading module.


FISO sensor on a US dime

SINGLE POINT Sensor - Light cable



Bare sensor: Item #**THR-NS-1165C**



Polyimide sheath with gel: Item# **THR-NS-1165E**



SINGLE POINT Sensor - Strong cable - tip Pl 200mm: Item #**THR-NS-1165B**(2m), **THR-NS-1165F**(10m)
- tip Pl 2mm: Item #**THR-NS-1165G**(2m), **THR-NS-1165H**(10m)



Preliminary

1. Custom temperature range may impact accuracy and resolution. Contact your representative for more details.
2. THR sensor and SPC-HR between 10 to 90°C: includes reproducibility (sensor/module interchangeability), repeatability and hysteresis, non-linearity, scale error, offset error, conditioner temperature compensation error.
3. Model dependent—contact your representative for more details

深圳市新世联科技有限公司

地址：深圳市深南中路2066号华能大厦712室
电话：0755-83680810 83680820 83680830 83680860
网址：www.apollounion.com
邮编：518031
传真：0755-83680866
邮箱：sales@apollounion.com